

This listing of claims will replace all prior versions, and listings, of claims in the application:

**LISTING OF THE CLAIMS:**

1. (Canceled)

2. (Currently amended) The method for supporting multifield classification according to Claim [[1]] 49, wherein the rule further comprises a field for specifying an action to be applied to the received fragment, the method further comprising a step of:

applying the action to the received fragment when the key matches the rule for the received fragment.

3. (Currently amended) The method for supporting multifield classification according to Claim [[1]] 49, further comprising the steps of:

receiving a packet at the forwarding platform; and

testing the received packet for determining whether the packet represents a fragment; and

performing the multifield classification of the received packet by matching a key derived from one or more fields of the received packet to a rule, the rule comprising a plurality of fields including at least one field for specifying whether the received packet's fragmentation characteristics are to be applied when performing the multifield classification.

4. (Currently Amended) The method for supporting multifield classification according to Claim [[1]] 49, further comprising the steps of:

determining whether there are any transfer control protocol (TCP) rules; and

performing the multifield classification if no TCP rules are indicated.

5. (Canceled)

6. (Currently Amended) The method for supporting multifield classification according to Claim [[5]] 49, wherein the preprocessing determines to forward the received fragment to a slow-speed forwarding platform.
7. (Currently Amended) The method for supporting multifield classification according to Claim [[5]] 49, wherein the preprocessing determines to discard the received fragment.
8. (Currently Amended) The method for supporting multifield classification according to Claim [[5]] 49, wherein the one or more flags are exclusive of one another.
9. (Currently Amended) The method for supporting multifield classification according to Claim [[1]] 49, wherein the one or more fields that comprise the key derived from the received fragment include fields from headers representing one or more transmission protocols.
10. (Original) The method for supporting multifield classification according to Claim 9, wherein the one or more transmission protocols include: Internet Protocol (IP); User Datagram Protocol (UDP); Internet Control Message Protocol (ICMP); and Internet Group Management Protocol (IGMP).
11. (Original) The method for supporting multifield classification according to Claim 9, wherein the one or more fields include: source address (SA), destination address (DA), protocol, fragmented flag (FRAG) and not subsequent flag (NO SUBS) from a header of an IP transmission protocol; and a source port (SP) and a destination port (DP) from a header of a TCP transmission protocol.
12. (Currently Amended) The method for supporting multifield classification according to Claim [[1]] 49, wherein a field in each rule comprises one or more values to be matched against the one or more fields of the derived key for the received fragment.
13. (Original) The method for supporting multifield classification according to Claim 12, wherein the one or more values represent an upper and a lower limit for a field in each rule.

14. (Currently Amended) The method for supporting multifield classification according to Claim [[1]] 49, wherein the one or more values represent a mask and a value.

15. (Currently Amended) The method for supporting multifield classification according to Claim [[1]] 49, wherein the plurality of rules are stored in the forwarding platform.

16. (Currently Amended) The method for supporting multifield classification according to Claim [[1]] 49, wherein the plurality of rules are stored in a rules database.

17. (Currently Amended) A wire-speed forwarding platform for supporting multifield classification of a packet fragmented into a plurality of fragments, the platform comprising:

- (a) media interface for receiving a fragment of the fragmented packet at the forwarding platform;  
a network processor having means for preprocessing the received fragment by querying a data structure in the forwarding platform; the data structure comprising one or more flags for determining whether the received fragment is to be classified in the forwarding platform and either redirecting or discarding the received fragment from the forwarding platform if it is determined that the received fragment is not to be classified at the forwarding platform; and
- (b) a said network processor for deriving a key from one or more fields of the received fragment; and performing multifield classification of the received fragment by matching the key to a rule out of a plurality of rules, the rule comprising a plurality of fields including at least one field for specifying whether the received fragment's fragmentation characteristics are to be applied when performing the multifield classification.

18. (Original) The wire-speed forwarding platform according to Claim 17, wherein the rule further comprises a field for specifying an action to be applied to the received fragment, the network processor further applying the action to the received fragment when the key matches the rule for the received fragment.

19. (Original) The wire-speed forwarding platform according to Claim 17, wherein the media interface further receives a packet at the forwarding platform, and the network processor tests the received packet for determining whether the packet represents a fragment and performs the multifield classification of the received packet by matching a key derived from one or more fields of the received packet to a rule, the rule comprising a plurality of fields including at least one field for specifying whether the received packet's fragmentation characteristics are to be applied when performing the multifield classification.

20. (Original) The wire-speed forwarding platform according to Claim 17, wherein the network processor further determines whether there are any transfer control protocol (TCP) rules and performs the multifield classification if no TCP rules are indicated.

21. (Canceled)

22. (Currently Amended) The wire-speed forwarding platform according to Claim ~~[[21]]~~ 17, wherein the preprocessing by the network processor determines to forward the received fragment to a slow-speed forwarding platform.

23. (Currently Amended) The wire-speed forwarding platform according to Claim ~~[[21]]~~ 17, wherein the preprocessing by the network processor determines to discard the received fragment.

24. (Currently Amended) The wire-speed forwarding platform according to Claim ~~[[21]]~~ 17, wherein the one or more flags are exclusive of one another.

25. (Currently Amended) The wire-speed forwarding platform according to Claim ~~[[1]]~~ 17, wherein the one or more fields that comprise the key derived from the received fragment include fields from headers representing one or more transmission protocols.

26. (Original) The wire-speed forwarding platform according to Claim 25, wherein the one or more transmission protocols include: Internet Protocol (IP); User Datagram Protocol (UDP); Internet Control Message Protocol (ICMP); and Internet Group Management Protocol (IGMP).

27. (Original) The wire-speed forwarding platform according to Claim 25, wherein the one or more fields include: source address (SA), destination address (DA), protocol, fragmented flag (FRAG) and not subsequent flag (NO SUBS) from a header of an IP transmission protocol; and a source port (SP) and a destination port (DP) from a header of a TCP transmission protocol.

28. (Original) The wire-speed forwarding platform according to Claim 17, wherein a field in each rule comprises one or more values to be matched against the one or more fields of the derived key for the received fragment.

29. (Original) The wire-speed forwarding platform according to Claim 28, wherein the one or more values represent an upper and a lower limit for a field in each rule.

30. (Original) The wire-speed forwarding platform according to Claim 17, wherein the one or more values represent a mask and a value.

31. (Original) The wire-speed forwarding platform according to Claim 17, wherein the plurality of rules are stored in the forwarding platform.

32. (Original) The wire-speed forwarding platform according to Claim 17, wherein the forwarding platform further comprises control memory associated with the network processor for storing a rules database comprising the plurality of rules.

33. (Currently Amended) A program storage device readable by a machine, tangibly embodying a program of instructions executable by the machine to perform the method steps for supporting multifield classification of a packet fragmented into a plurality of fragments in a wire-speed forwarding platform, the method comprising:

(a) receiving a fragment of the fragmented packet at the forwarding platform and deriving a key from one or more fields of the received fragment;

(b) preprocessing the received fragment by querying a data structure that comprises one or more flags for determining whether the received fragment is to be classified in the forwarding platform;

(c) redirecting or discarding the received fragment from the forwarding platform if it is determined that the received fragment is not to be classified at the forwarding platform;  
and

[[ (b) ] ] (d) performing multifold classification of the received fragment by matching the key to a rule out of a plurality of rules, the rule comprising a plurality of fields including at least one field for specifying whether the received fragment's fragmentation characteristics are to be applied when performing the multifold classification.

34. (Currently Amended) The ~~method for supporting multifold classification~~ program storage device according to Claim 33, wherein the rule further comprises a field for specifying an action to be applied to the received fragment, the method further comprising a step of:

applying the action to the received fragment when the key matches the rule for the received fragment.

35. (Currently Amended) The ~~method for supporting multifold classification~~ program storage device according to Claim 33, further comprising the steps of:

receiving a packet at the forwarding platform; and  
testing the received packet for determining whether the packet represents a fragment; and  
performing the multifold classification of the received packet by matching a key derived from one or more fields of the received packet to a rule, the rule comprising a plurality of fields including at least one field for specifying whether the received packet's fragmentation characteristics are to be applied when performing the multifold classification.

36. (Currently Amended) The ~~method for supporting multifold classification~~ program storage device according to Claim 33, further comprising the steps of:

determining whether there are any transfer control protocol (TCP) rules; and  
performing the multifold classification if no TCP rules are indicated.

37 (Canceled).

38. (Currently Amended) The ~~method for supporting multifield classification~~ program storage device according to Claim ~~[[37]]~~ 33, wherein the preprocessing determines to forward the received fragment to a slow-speed forwarding platform.

39. (Currently Amended) The ~~method for supporting multifield classification~~ program storage device according to Claim ~~[[37]]~~ 33, wherein the preprocessing determines to discard the received fragment.

40. (Currently Amended) The ~~method for supporting multifield classification~~ program storage device according to Claim ~~[[37]]~~ 33, wherein the one or more flags are exclusive of one another.

41. (Currently Amended) The ~~method for supporting multifield classification~~ program storage device according to Claim 33, wherein the one or more fields that comprise the key derived from the received fragment include fields from headers representing one or more transmission protocols.

42. (Currently Amended) The ~~method for supporting multifield classification~~ program storage device according to Claim 41, wherein the one or more transmission protocols include: Internet Protocol (IP); User Datagram Protocol (UDP); Internet Control Message Protocol (ICMP); and Internet Group Management Protocol (IGMP).

43. (Currently Amended) The ~~method for supporting multifield classification~~ program storage device according to Claim 41, wherein the one or more fields include: source address (SA), destination address (DA), protocol, fragmented flag (FRAG) and not subsequent flag (NO SUBS) from a header of an IP transmission protocol; and a source port (SP) and a destination port (DP) from a header of a TCP transmission protocol.

44. (Currently Amended) The ~~method for supporting multifield classification~~ program storage device according to Claim 33, wherein a field in each rule comprises one or more values to be matched against the one or more fields of the derived key for the received fragment.

45. (Currently Amended) The ~~method for supporting multifield classification~~ program storage device according to Claim 44, wherein the one or more values represent an upper and a lower limit for a field in each rule.

46. (Currently Amended) The ~~method for supporting multifield classification~~ program storage device according to Claim 33, wherein the one or more values represent a mask and a value.

47. (Currently Amended) The ~~method for supporting multifield classification~~ program storage device according to Claim 33, wherein the plurality of rules are stored in the forwarding platform.

48. (Currently Amended) The ~~method for supporting multifield classification~~ program storage device according to Claim 33, wherein the plurality of rules are stored in a rules database.

49. (Original) A method for supporting multifield classification of a packet fragmented into a plurality of fragments in a wire-speed forwarding platform, the method comprising:

(a) receiving a fragment of the fragmented packet at the forwarding platform and deriving a key from one or more fields of the received fragment;

(b) preprocessing the received fragment by querying a data structure that comprises one or more flags for determining whether the received fragment is to be classified in the forwarding platform;

(c) redirecting or discarding the received fragment from the forwarding platform if it is determined that the received fragment is not to be classified at the forwarding platform; and

(d) performing multifield classification of the received fragment by matching the key to a rule out of a plurality of rules, the rule comprising a plurality of fields including at least



one field for specifying whether the received fragment's fragmentation characteristics are to be applied when performing the multifield classification.

50. (Original) A method for supporting multifield classification of a packet fragmented into a plurality of fragments in a wire-speed forwarding platform, the method comprising:

(a) receiving a fragment of the fragmented packet at the forwarding platform and deriving a key from one or more fields of the received fragment;

(b) determining whether there are transfer control protocol (TCP) rules and if it is determined that there are no TCP rules indicated performing multifield classification of the received fragment according to step (d);

(c) preprocessing the received fragment if there are TCP rules by querying a data structure that comprises one or more flags for determining whether the received fragment is to be classified in the forwarding platform and redirecting or discarding the received fragment from the forwarding platform if it is determined that the received fragment is not to be classified at the forwarding platform; and

(d) performing multifield classification of the received fragment by matching the key to a rule out of a plurality of rules, the rule comprising a plurality of fields including at least one field for specifying whether the received fragment's fragmentation characteristics are to be applied when performing the multifield classification.